

PATENT COOPERATION TREATY

PCT

NOTIFICATION OF ELECTION

(PCT Rule 61.2)

From the INTERNATIONAL BUREAU

To:

United States Patent and Trademark
Office
(Box PCT)
Crystal Plaza 2
Washington, DC 20231
ÉTATS-UNIS D'AMÉRIQUE

in its capacity as elected Office

Date of mailing (day/month/year) 26 February 1999 (26.02.99)	
International application No. PCT/US98/12823	Applicant's or agent's file reference IOLL-281PC
International filing date (day/month/year) 19 June 1998 (19.06.98)	Priority date (day/month/year) 20 June 1997 (20.06.97)
Applicant ZHANG, Li	

1. The designated Office is hereby notified of its election made:

☒ in the demand filed with the International Preliminary Examining Authority on:19 January 1999 (19.01.99)☐ in a notice effecting later election filed with the International Bureau on:2. The election ☒ was☐ was not

made before the expiration of 19 months from the priority date or, where Rule 32 applies, within the time limit under Rule 32.2(b).

The International Bureau of WIPO
34, chemin des Colombettes
1211 Geneva 20, Switzerland

Facsimile No.: (41-22) 740.14.35

Authorized officer

Marie-José Devillard

Telephone No.: (41-22) 338.83.38

PATENT COOPERATION TREATY

PCT

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

(PCT Article 36 and Rule 70)

REC'D 05 OCT 1999
WIPO PCT


Applicant's or agent's file reference IOLL-281PC	FOR FURTHER ACTION See Notification of Transmittal of International Preliminary Examination Report (Form PCT/IPEA/416)	
International application No. PCT/US98/12823	International filing date (day/month/year) 19 JUNE 1998	Priority date (day/month/year) 20 JUNE 1997
International Patent Classification (IPC) or national classification and IPC Please See Supplemental Sheet.		
Applicant IONICS, INCORPORATED		

1. This international preliminary examination report has been prepared by this International Preliminary Examining Authority and is transmitted to the applicant according to Article 36.
2. This REPORT consists of a total of 9 sheets.
- ☒ This report is also accompanied by ANNEXES, i.e., sheets of the description, claims and/or drawings which have been amended and are the basis for this report and/or sheets containing rectifications made before this Authority. (see Rule 70.16 and Section 607 of the Administrative Instructions under the PCT).

These annexes consist of a total of 4 sheets.

3. This report contains indications relating to the following items:

- I ☒ Basis of the report
- II ☐ Priority
- III ☐ Non-establishment of report with regard to novelty, inventive step or industrial applicability
- IV ☐ Lack of unity of invention
- V ☒ Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement
- VI ☐ Certain documents cited
- VII ☒ Certain defects in the international application
- VIII ☒ Certain observations on the international application

Date of submission of the demand 19 JANUARY 1999	Date of completion of this report 06 AUGUST 1999
Name and mailing address of the IPEA/US Commissioner of Patents and Trademarks Box PCT Washington, D.C. 20231	Authorized officer  ANA FORTUNA
Facsimile No. (703) 305-3230	Telephone No. (703) 308-3857

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

International application No.

PCT/US98/12823

I. Basis of the report

1. This report has been drawn on the basis of *(Substitute sheets which have been furnished to the receiving Office in response to an invitation under Article 14 are referred to in this report as "originally filed" and are not annexed to the report since they do not contain amendments):*

☐ the international application as originally filed.

☒ the description, pages (See Attached) , as originally filed.

pages _____ , filed with the demand.

pages _____ , filed with the letter of _____.

pages _____ , filed with the letter of _____.

☒ the claims, Nos. (See Attached) , as originally filed.

Nos. _____ , as amended under Article 19.

Nos. _____ , filed with the demand.

Nos. _____ , filed with the letter of _____.

Nos. _____ , filed with the letter of _____.

☒ the drawings, sheets/fig (See Attached) , as originally filed.

sheets/fig _____ , filed with the demand.

sheets/fig _____ , filed with the letter of _____.

sheets/fig _____ , filed with the letter of _____.

2. The amendments have resulted in the cancellation of:

☒ the description, pages NONE .

☒ the claims, Nos. NONE .

☒ the drawings, sheets/fig NONE .

3. ☐ This report has been established as if (some of) the amendments had not been made, since they have been considered to go beyond the disclosure as filed, as indicated in the ~~Supplemental Box~~ Additional observations below (Rule 70.2(c)).

4. Additional observations, if necessary:

NONE

V. Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement**1. STATEMENT**

Novelty (N)	Claims	<u>8, 11, 20, 23</u>	YES
	Claims	<u>1-7, 9-10, 12-19, 21-22</u>	NO
Inventive Step (IS)	Claims	<u>NONE</u>	YES
	Claims	<u>1-23</u>	NO
Industrial Applicability (IA)	Claims	<u>1-23</u>	YES
	Claims	<u>NONE</u>	NO

2. CITATIONS AND EXPLANATIONS

Claims 1-4, 6, 7, 12-16 and 18 lack novelty under PCT Article 33(2) as being anticipated by Kawai et al (4,863,608). Reference '608 discloses the process of treating and purifying water including oxidation or UV sterilization, microfiltration, ion exchange resin treatment, reverse osmosis, etc. The combination of process steps including the particular units as claimed in the claims above have been disclosed by reference '608 as conventional in the art (column 1, lines 37-68, column 2, lines 1-11)., e.g. reverse osmosis UV light radiation, and ion exchange, between others. Reference '608 further discloses the combination of UV radiation with catalyst for further improvement in removing carbon compounds, therefore the process is more effective in the second step for removing or decomposing carbon compounds, but UV radiation alone is also disclosed as conventional method in the art for removing the same type of compound claimed (column 3, lines 51-68, column 4, lines 1-58).

Claims 1-6, 7, 9, 10, 12-19 and 21-22 lack novelty under PCT Article 33(2) as being anticipated by JP61101292, JP53149873, or Cooper et al (5,118,422). Reference '292 discloses the apparatus and process of removing organic substances from water, the process include radiation, ion exchange, second step radiation, and a second step ion exchange, therefore, the conditions of claim 2 having the first and second removal apparatus comprising the second removal apparatus is met. The first removal and second removal apparatus in the particular reference will be the ion exchange, the first radiation will be a preliminary treatment, which will not be excluded from the claims limitations (Abstract). Reference '873 discloses removing organic matter from water to produce water of high purity by the combination of reverse osmosis irradiating with UV light in the presence of hydrogen peroxide, and further treating with ion exchange resin (abstract). Reference '422 discloses the treatment of permeate from reverse osmosis membrane by ultraviolet driven photocatalytic post-treatment (Abstract). Regarding claim 5, reference '422 discloses employing UV light of the order of 185 nm in photocatalytic (Continued on Supplemental Sheet.)

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

International application No.

PCT/US98/12823

VII. Certain defects in the international application

The following defects in the form or contents of the international application have been noted:

The description is objected to as containing the following defect(s) under PCT Rule 66.2(a)(iii) in the form or contents thereof: in the specification, page 5, third paragraph, ste (c) shoul be corrected.

VIII. Certain observations on the international application

The following observations on the clarity of the claims, description, and drawings or on the question whether the claims are fully supported by the description, are made:

Claims 2, 3, 13, 14 are objected to under PCT Rule 66.2(a)(v) as lacking clarity under PCT Article 6 because the claims are indefinite for the following reason(s): the terms first removal means comprising the second removal means is unclear as to whether on unit is part of the other, or as the same unit is intended. The term "other sorbent apparatus is indefinite regarding to what apparatus it refers to.

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

International application No.

PCT/US98/12823

Supplemental Box

(To be used when the space in any of the preceding boxes is not sufficient)

Continuation of: Boxes I - VIII

Sheet 10

CLASSIFICATION:

The International Patent Classification (IPC) and/or the National classification are as listed below:

IPC(6): BO1D 61/00, 15/00 and US Cl.: 210/652, 638, 760,644, 661, 663, 900, 263, 195.2, 257.2, 204/157.62, 164

I. BASIS OF REPORT:

This report has been drawn on the basis of the description,
pages, 1-13, as originally filed.
pages, NONE, filed with the demand.
and additional amendments:
NONE

This report has been drawn on the basis of the claims,
numbers, NONE, as originally filed.
numbers, NONE, as amended under Article 19.
numbers, NONE, filed with the demand.
and additional amendments:
Claims 1-23, filed with the letter of 23 June 1993.

This report has been drawn on the basis of the drawings,
sheets, 1-4, as originally filed.
sheets, NONE, filed with the demand.
and additional amendments:
NONE

V. 2. REASONED STATEMENTS - CITATIONS AND EXPLANATIONS (Continued):

decomposition of organics in water (column 7, lines 19-37), and further discloses the factors affecting the degree of destruction of organics, e.g. degree of light adsorption, and rapid de-excitation of the molecules. Therefore, the combination of irradiation with UV light at 185 nm with catalyst, e.g. titanium oxide is suggested. Reference '422 also discloses a second removal step, e.g. removal by cross flow filtration and purified water collection and can be applied to at least claims 1, 3, 4, 5, 6, 7, 9-10, 12, 13-19, 21-22. Regarding claims 7 and 19, generation of hydrogen peroxide in the process is disclosed by '422 (column 4, lines 51-63).

Claims 1, 3-6, 12 and 14-19 lack an inventive step under PCT Article 33(3) as being obvious over Berry, III, et al. (4,280,912). Berry et al discloses the process and apparatus claimed including units from treating ionized and non-ionized compounds, e.g. ion exchange units, ultraviolet treatment and resin polishing bed treatment, e.g. mixed bed ion-exchange treatment, the process also includes prefiltering with micro filters (columns 1-6).

Claims 8, 11, 20 and 23, lack an inventive step under PCT Article 33(3) as being obvious over JP61101292, JP53149873 or 5,118422art as applied in the paragraph above. The references as discussed above fail to disclose the combination of process including ozone or mixtures of ozone and hydrogen peroxide. It would have been obvious to one skilled in the pertinent art combine a mixture of conventionally known oxidation agents, e.g. to improve the oxidation process. Hydrogen peroxide is generated by the process of irradiation and catalyst, the prior art discussed above also discloses irradiation in presence of hydrogen peroxide, it would have been obvious to one skilled in the pertinent art to substitute a well known oxidation agent by an equivalent oxidation agent, or the result can be expected to the ordinary skilled in the art.

----- NEW CITATIONS -----

US 5,118,422 A (COOPER et al) 02 June 1992, entire disclosure.

JP 53149873 A (KURITA WATER IND LTD) 27 December 1978, abstract.


JP 61101292 A (KURITA WATER IND LTD) 20 May 1986, abstract.



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : B01D 61/00, 15/00	A1	(11) International Publication Number: WO 98/58727 (43) International Publication Date: 30 December 1998 (30.12.98)
(21) International Application Number: PCT/US98/12823 (22) International Filing Date: 19 June 1998 (19.06.98) (30) Priority Data: 60/050,376 20 June 1997 (20.06.97) US (71) Applicant (for all designated States except US): IONICS, INCORPORATED [US/US]; 65 Grove Street, Watertown, MA 02172 (US). (72) Inventor; and (75) Inventor/Applicant (for US only): ZHANG, Li [-/US]; 26 Smith Street, Westborough, MA 01581 (US). (74) Agents: LAPPIN, Mark, G. et al.; Lappin & Kusmer LLP, 200 State Street, Boston, MA 02109 (US).		(81) Designated States: JP, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>

(54) Title: FLUID PURIFICATION DEVICES AND METHODS EMPLOYING DEIONIZATION FOLLOWED BY IONIZATION FOLLOWED BY DEIONIZATION

**(57) Abstract**

The invention provides the continuous, integrated methods and devices for substantially removing ionized and ionizable carbon compounds from an aqueous stream by first deionization step to produce a first product stream, ionizing nonionized and nonionizable carbon compounds in such stream to form further ionized and ionizable compounds, and removing the latter by a second deionization step. The method can be performed for example in an apparatus including an EDI unit (10), an ionizing unit (60), and EDI unit (100).

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

**FLUID PURIFICATION DEVICES AND METHODS
EMPLOYING DEIONIZATION FOLLOWED BY
IONIZATION FOLLOWED BY DEIONIZATION**

5 This invention relates to fluid purification using deionization and ionization processes and devices. More specifically, the invention relates to the substantial removal of carbon compounds from water by such processes and devices.

BACKGROUND OF THE INVENTION

10 Electrodialysis (ED), electrodeionization (EDI) and related methods and devices were initially developed during the 1950s, and have since that time been improved to the point that such systems are commonly employed to purify fluids for a variety of applications. In general, ED, EDI, and related methods and devices purify fluids through electric field-mediated transfer of ions
15 through membranes from diluting streams passing through "less concentrated", ion depleting compartments to concentrating or brine streams passing through "more concentrated", ion concentrating compartments. Generally, anion transfer (i.e. cation rejecting) and cation transfer (i.e. anion rejecting) membranes are alternated in ED and EDI methods and devices, the membranes being placed between an anode (positive electrode) and a cathode (negative electrode) across which
20 a DC electric field is applied transverse to the fluid flow directions. Anion transfer membranes allow passage only of low molecular weight negatively charged species (anions), and cation transfer membranes allow passage only of low molecular weight positively charged species (cations). Transfer of ions across membranes is mediated by the attraction of the anions to the positively charged anode and the cations to the negatively charged cathode. The combination of an anode, a
25 cathode, and the alternating anion and cation transfer membranes there between is commonly referred to as an ED or EDI "stack". Such stacks may also include cation or anion transfer membranes alternating with substantially non-ion-selective membranes, that is membranes which are not substantially selective for either anions or cations.

30 EDI differs from ED in that one or more EDI compartments formed by membranes include ion exchange media. The media, typically in the form of resin fibers, fabrics, beads or granules, is present in diluting compartments and sometimes also in concentrating compartments of an EDI device. An EDI compartment may contain either cation exchange resins, anion exchange resins, or a random or structured combination of cation exchange resins and anion exchange resins. The resins reside in the space between alternating anion and cation transfer membranes. In response to the

transverse DC electric field, ions are transferred, for example, from diluting to concentrating compartments via the diluting compartment resins and adjacent membranes. The resins form a conductive bridge for movement of ions associated therewith to the ion exchange membranes and thus out of the diluting compartment. The resin facilitates mass transfer of ions by increasing the area available for mass transfer and by decreasing the distance in solution that the ions must travel in order to be removed from the diluting compartment, thus reducing the electrical resistance of the unit, especially in the diluting compartment. In EDI, as the product becomes more pure, the electric field splits water to hydrogen and hydroxide ions which continuously regenerate the membranes and the resins at least in part. The main advantages of EDI processes include continuous operation; stable product quality; the ability to produce high purity product without requiring periodic chemical regeneration; and reduced amounts of waste products.

One area in which EDI technology is gaining momentum is production of ultrapure makeup water for electric power plants. EDI was initially used in the electric power industry in 1991, and since that time more than 50 EDI devices have been installed in such plants. In these plants, EDI has partially or completely replaced the prior conventional (i.e. chemically regenerated) ion exchange resin beds, resulting in substantial operating cost savings. For example, ion exchange units are frequently used to purify blowdown (waste water) for recycling, requiring frequent regeneration, consuming large volumes of acid and caustic, and necessitating constant maintenance. Such exhaustion (degeneration) and regeneration can also result in variations in demineralization performance, thus affecting reliability of use. With the advent of EDI systems, deionization and regeneration are simultaneous and continuous, and problems associated with periodic regeneration are no longer present.

EDI is highly efficient in removing a substantial variety of ions from water. Strongly ionized substances such as sodium, calcium, magnesium, chloride, fluoride and sulfate are examples of ions which are routinely substantially completely removed from water using multi-step purification systems which include one or more EDI units. Weakly ionizable species such as CO₂, silica, boric acid and ammonia may also be removed using EDI. Similarly, ethanolamine (ETA) and methoxypropylamine (MPA) are also readily removed by EDI. However, complete removal of non-ionized and non-ionizable organic substances such as ethanol and glyoxal, is not as easily accomplished.

U.S. Patent No. 5,116,509 discloses use of an ultraviolet (UV) treatment step for deionized tap water prior to EDI treatment, but fails to teach or to suggest a system which processes such tap

water water initially containing non-ionized or non-ionizable carbon compounds in addition to ionic or ionizable organic species. "Substantially complete removal" of total organic carbon (TOC) is purported to have been obtained using the system of U.S. Pat. No. 5,116,509. The patent teaches that following an initial deionization, organic species may be added to the deionized tap water and applied UV may break down the added organic species into smaller molecules, some of which are ionic and/or ionizable, allowing subsequent EDI to achieve the claimed TOC reduction. When some part of the added organic species is already in ionic and/or ionizable form, the claims for such a process may not be totally true, however. Although UV may convert non-ionizable organic species into ionic and/or ionizable organic species, UV may also convert ionic and/or ionizable organic species into non-ionizable organic species. If a significant amount of the organic species is in ionic and/or ionizable forms, application of UV may increase the concentration of non-ionizable organic species in the subsequent EDI feed, and may result in a lower organic carbon reduction than without UV. Further, the ionic or ionizable organic species may absorb UV further reducing UV available for converting non-ionizable organic species into ionic or ionizable organic species.

A need remains, therefore, for additional methods and devices capable of obtaining improved purity product from purification systems. In particular, additional methods and devices are needed which can remove non-ionized or non-ionizable carbon compounds in multi-step purification systems.

SUMMARY OF THE INVENTION

The invention is directed to methods and devices for removing substantially all inorganic and organic carbon compounds from water. In accordance with the present invention, one or more first deionization stages remove ionic and/or ionizable contaminants. The product stream of such first deionization stages is exposed to an organic carbon bond-breaking agent prior to becoming the feed stream of one or more second deionization stages. Such exposure causes non-ionized organic carbon compounds in the first deionization product stream to ionize or become ionizable, facilitating removal in such second deionization stages. Further, since ionic and/or ionizable contaminants are substantially removed in the first deionization stages, the amount of bond breaking agent required to convert the non-ionizable organic carbon compounds to ionic or ionizable organic carbon compounds is minimized.

In accordance with the invention, such first one or more deionization stages remove the ionic and/or ionizable inorganic and organic carbon species. The effluent from such first deionization

stages is exposed to organic carbon bond-breaking agents, such as UV (preferably 184.9 nm wavelength or less) including catalyzed UV and/or other oxidizing agents (e.g., oxygen, ozone, singlet oxygen, hydrogen peroxide, hydroxide radical, means to produce singlet oxygen or hydroxide radical or combinations thereof). These agents break down organic carbon compounds from such first deionization stages. With the subject invention, it is not necessary to provide a level of UV energy sufficient to break down organic components all the way to H₂O and CO₂, but rather it is sufficient to break down those components into compounds which may be removed in subsequent removal stage(s).

In one embodiment, the invention provides a method of removing inorganic and organic carbon contaminants from water. The method involves the steps of: flowing such water through one or more first removal units to produce a first product stream having less organic carbon compounds; exposing such first product stream for a predetermined time to an organic carbon bond-breaking agent (preferably at a predetermined temperature) sufficient to produce a second product stream containing at least a portion of the remaining organic carbon compounds in an ionized or ionizable form; and flowing such second product stream containing such organic carbon compounds in ionized or ionizable form through one or more second removal units, wherein such organic carbon compounds in ionized or ionizable form are substantially removed. Such removal units may be independently selected from reverse osmosis (RO), nanofiltration (NF), electrodialysis (ED), electrodeionization (EDI), filled cell electrodialysis, and electrodiaresis devices; chemically or electrically regenerable ion exchange (IX) systems; and activated carbon and other sorbent beds.

In another embodiment, the invention provides a device for removing organic carbon compounds from water. The device involves: a first electrodeionization (EDI) unit having at least one diluting compartment extending in fluid communication between a first feed stream inlet and a first product stream outlet; a second EDI unit having at least one diluting compartment extending in fluid communication between a second feed stream inlet and a second product stream outlet; a fluid flow path coupling the first product stream outlet and the second feed stream inlet; and an ionizing unit for exposing a fluid flowing along such fluid flow path to at least one organic carbon bond-breaking agent thereby providing substantial removal of organic carbon compounds in the second deionization unit.

It will be understood that such second stages for removing ionized and/or ionizable carbon species may in fact be the same device as that used for the first stage for removing such species. For example, the fluid may be contacted with one or more first stages for removing ionized and/or ionizable carbon species, then contacted with such an organic carbon bond-breaking device and

subsequently recycled to such first stages for removing ionizable and/or ionized carbon species. Such combination of bond-breaking and removal devices may operate on batch or on feed-and-bleed continuous bases.

In yet another embodiment, the invention provides a method for removing both ionizable and/or ionized carbon compounds, and non-ionized and/or non-ionizable carbon compounds from water. The method involves the steps of (a) processing a first stream of the water with a removal apparatus for removing ionized and/or ionizable carbon compounds from the water to produce a first product stream; (b) contacting the first product stream with an agent for converting non-ionized and/or non-ionizable carbon compounds into ionized and/or ionizable carbon compounds to form a second product stream; (c) processing the second product stream with a second removal apparatus for removing ionized and/or ionizable carbon compounds from the water to form a third product stream; and (d) recovering the third product stream from step (c). In alternative embodiments, the method includes the steps of recovering the first product stream from step (a) and recovering the second product stream from step (b).

In still another embodiment, the invention provides a device for removing both ionizable and/or ionized carbon compounds, and non-ionized and/or non-ionizable carbon compounds from water. The device involves (a) a first removal means for removing ionized and/or ionizable carbon compounds from the water to produce a first product stream; (b) a conversion means for converting non-ionized and/or non-ionizable carbon compounds in the first product stream into ionized and/or ionizable carbon compounds to form a second product stream; (c) a second removal means for removing ionized and/or ionizable carbon compounds from the second product stream to form a third product stream; and (d) a recovery means for recovering the third product stream. In alternative embodiments, the device also includes a second recovery means for recovering the first product stream and a third recovery means for recovering the second product stream.

It will also be understood that "organic carbon in an ionized or ionizable form" includes carbon dioxide, bicarbonate and/or carbonate which results from the bond-breaking of an organic carbon species.

As used herein, the term "ionizable" as in, for example, organic carbon in an ionizable form, refers to organic carbon which can be ionized by proximity to the surface of ion exchange media.

BRIEF DESCRIPTION OF THE DRAWING

The foregoing and other objects of the invention, the various features thereof, as well as the invention itself, may be more fully understood from the following description, when read together with the accompanying drawings in which:

FIG. 1 is a schematic diagram of an electrodeionization device (prior art);

FIG. 2 is a schematic depiction of one embodiment of the apparatus of the invention;

FIG. 3 is a graph showing removal of organic carbon compounds from a product stream of a purification system applied to a waste stream of a steam generator, according to an embodiment of the invention; and

FIG. 4 is a representative curve showing calculated concentrations of organic carbon compounds removed from a steam generator water circulation loop, according to an embodiment of the invention.

DETAILED DESCRIPTION OF SOME PREFERRED EMBODIMENTS

In accordance with the invention, inorganic and organic carbon compounds are substantially removed from water using a two-stage deionization device, having an organic carbon ionizing unit interposed between the two stages in such a way that the product stream of the first deionization stage is exposed to one or more organic carbon bond-breaking agents. At least some organic carbon compounds in the product stream of the first stage are ionized or rendered ionizable prior to transfer to the feed stream of the second deionization stage. Alternatively, after exposure to one or more carbon bond-breaking agents, the ionized or ionizable stream is recycled back to the first deionization stage.

The term "conversion agent", as defined herein, refers to an agent capable of converting non-ionized and nominally non-ionizable carbon compounds to ionized and ionizable compounds. Conversion agents include bond-breaking agents such as oxidizing and reducing agents. Examples of oxidizing agents include chemical oxidizing agents, electrolytic oxidizing agents, thermal oxidizing agents (heat), radiation and/or catalysts, and combinations thereof. Preferably, the oxidation agent includes ultraviolet (UV) radiation. More preferably, the UV radiation is characterized by wavelengths of about 184.9 nm or less wave lengths. Such radiation can be used in conjunction with a catalyst such as titanium dioxide. Alternatively, more preferably the UV

radiation is characterized by wavelengths of about 254 nm and used in conjunction with a catalysts, such as, for example, titanium dioxide.

The term "deionization", as used herein, refers to devices and associated methods for removing ionizable and/or ionized organic carbon and other ionizable and/or ionized compounds from fluids for purification purposes. Exemplary deionization devices and methods include reverse osmosis (RO), nanofiltration (NF), electrodialysis (ED), electrodeionization (EDI), filled cell electrodialysis, and electrodiuresis devices; chemically or electrically regenerable ion exchange (IX) systems; and activated carbon and other sorbent beds. The ion exchange systems may be liquid or solid, organic or inorganic.

The term "substantial removal" of organic carbon compounds, as used herein, refers to the removal of organic carbon compounds in the range of about 50% to about 100%, and preferably in the range of about 70% to about 100%, and most preferably in the range of about 80% to about 100%.

The methods and devices disclosed herein may be used *per se*, or they may be combined with other purification means to optimize the purity and cost of the effluent product. Performance of any purification system may be improved using the methods and devices of the present invention, whether the disclosed system is used as a part of a multi-step purification system, or is used alone. The performance of multi-step purification systems i.e., systems in which a variety of purification methodologies are employed, is particularly improved using the methods and devices of the present invention.

The present invention is described in terms of a two-stage deionization system which includes two EDI units. It should be understood, however, that other types of deionization devices such as reverse osmosis, nanofiltration, ED, filled cell ED and electrodiuresis devices; activated carbon or other sorbent devices; and/or chemically or electrically regenerable ion exchange resin systems can also be substituted for one or both EDI units described herein. Further, each stage may consist of two or more deionization units in series and/or in parallel.

FIG. 1 depicts a schematic view of an EDI unit 10 known in the art, having a cathode 12 and an anode 14 and a plurality of cation transfer membranes 20 alternating with anion transfer membranes 22. Cation transfer membranes 20 and anion transfer membranes 22 form alternating diluting compartments 24 and concentrating or brine compartments 26. Either or both of the diluting compartments 24 and concentrating or brine compartments 26 are filled with ion exchange resins. The diluting compartments 24 may be filled with an ion exchange resin, a mixture of anion and cation exchange resins or with layers of such resins. A fluid, preferably water containing salt, enters

unit 10 at electrode stream inlets 52 and exits unit 10 at electrode stream outlets 54 to form electrode streams 50.

Fluid to be purified flows into EDI unit 10 in the form of feed stream 30 which enters the unit at inlet 32. Feed stream inlet 32 is in fluid communication with feed stream inlet manifold 34, through which fluid to be purified is delivered to one or more diluting compartments 24. The number of diluting compartments 24 in an EDI unit may vary according to the application in which the unit is used. Determinations of the appropriate number of diluting compartments for a particular application may be accomplished empirically, on the basis of the desired flow and deionization capacity of the fluid purification system and the amount and identity of contaminants in the feed stream. As defined herein, diluting compartment 24 of unit 10 involves the sum, collectively, of all diluting compartments contained within the unit. After traversing the diluting compartment 24, fluid from feed stream 30 enters product stream outlet manifold 36, exiting the unit as product stream 30a at product stream outlet 38. Fluid is purified in diluting compartments 24 by virtue of passage of ions out of such diluting compartments into the concentrating or brine compartments 26.

A concentrate or brine influent 40 flows into unit 10 at concentrate or brine stream inlet 42. Concentrate or brine stream inlet 42 is in fluid communication with concentrate or brine stream inlet manifold 44, through which fluid that receives ions from the diluting compartments 24 is delivered to one or more concentrating or brine compartments 26. The number of concentrating or brine compartments in an EDI unit may vary according to the application in which the unit is used, but will be equal to (or ± 1) the number of diluting compartments in the unit. As defined herein, concentrating or brine compartment 26 of unit 10 involves the sum, collectively, of all concentrating or brine compartments contained within the unit. After traversing concentrating compartment 26, fluid from concentrate or brine influent 40 enters concentrate or brine stream outlet manifold 46, exiting the unit at EDI concentrate or brine stream outlet 48. After exiting from concentrate or brine stream outlet 48, a portion of the brine stream may be discarded as "blowdown", and the remainder recycled into concentrate or brine influent 40, upstream of brine stream inlet 42.

FIG. 2 shows an embodiment of the device of the invention in which feed stream 30 flows into first EDI feed stream inlet 32 and out of first EDI product stream outlet 38, as deionized product 80, described in detail above. Product stream 30a then flows into ionizing unit 60 via ionizing unit inlet 62.

Different bond-breaking agents can be used in the ionizing unit 60 to ionize organic species in product stream 30a in accordance with the invention. For example, the ionizing unit 60 can include an element 61 for adding a bond-breaking agent 63 to the product stream 30a. Such bond-

breaking agents 63 can include, but are not limited to, chemical oxidizing agents capable of generating oxidizing free radicals when added to product stream 30a. Many compounds capable of generating oxidizing free radicals known to those of ordinary skill in the art, such as, for example, peracetic acid and persulfate compounds, are suitable as ionizing agents in accordance with the invention. Compounds which ultimately yield only water or readily removeable innocuous byproducts are preferred. For example, oxygen, singlet oxygen, ozone or hydrogen peroxide, or combinations thereof, are particularly suitable as oxidizing free radical generating compounds. Such oxidizing agents can be used in conjunction with catalysts, preferably insoluble catalysts such as finely divided supported platinum or platinum group metals, oxides of these metals or other compounds containing these metals.

Bond-breaking agents 63 which can be used in ionizing unit 60 for ionizing product stream 30a in accordance with the invention also include electrolytic oxidizing agents. Non-limiting examples of such electrolytic oxidizing agents include lead oxide or tin oxide anodes. Other electrolytic oxidizing agents known to those of ordinary skill in the art can also be used for oxidizing product stream 30a.

Further bond-breaking agents 63 which can be used in accordance with the invention include catalytic oxidizing agents. Product stream 30a can be contacted with a catalyst rich surface including rare earth catalysts, or platinum catalysts.

Ionizing unit 60 can further include an element 65 for exposing the product stream 30a, including non-ionized and/or non-ionizable organic species, to a bond-breaking agent 63 such as radiation 66. Any kind of radiation 66 is suitable as a bond-breaking agent 63, so long as the radiation is of sufficient energy to break down at least a portion of the non-ionized or non-ionizable organic species to yield ionized species. Preferably UV radiation is used. More preferably, the UV radiation used is in the range of from about 160 nm to about 260 nm. Most preferably, the UV radiation is characterized by wavelengths of about 184.9 nm or less. UV catalysts, such as titanium dioxide may be used in conjunction with such radiation. Alternatively, most preferably UV radiation characterized by wavelengths of about 254 nm is used in conjunction with catalyst such as, for example, titanium dioxide. UV radiation, with or without catalyst, may be used in the absence of other oxidizing agents provided the concentration of organic carbon compounds is low e.g., 1 ppm or less. Suitable sources of UV include low, medium or high pressure mercury arc lamps; doped mercury arc lamps; incoherent or coherent excimer lamps such as, for example, Xenon(172 nm), Argon chloride (175 nm), Argon fluoride (193 nm), Krypton chloride (222 nm), Krypton fluoride

(249 nm) and other gas discharge lamps. It is preferred such sources include a substantial amount of radiation in the range of about 160 nm to about 260 nm.

Ionizing unit 60 can also include an element 67 for heating the product stream 30a to oxidize the non-ionized or non-ionizable organic carbon species of product stream 30a to form ionizable species. In such an embodiment, heat serves as a thermal oxidizing agent.

Exposure to the bond-breaking agent occurs for a predetermined time period ranging from about 1 second to about 100 minutes, and at a temperature (which may be a predetermined) ranging from about 5° C to about 400° C, depending upon the type of bond-breaking agent employed and thus refractoriness of the organic species. Different bond-breaking agents, such as those exemplary agents exemplified above, can be used alone or in various combinations of two or more, with or without catalysts and/or carriers and/or supports.

After exposure to the bond-breaking agent 63, product stream 130 exits ionizing unit 60 through ionizing unit outlet 64 and flows into the second EDI unit 100 via feed stream inlet 132. Organic carbon compounds which have been oxidized to ionized or ionizable compounds by ionizing unit 60 will be removed in the diluting stream of second EDI unit 100. Thus, second product stream 130a exits such second EDI unit 100 through product stream outlet 138 substantially free of organic carbon species. Alternatively, product stream 130 is recycled back to EDI unit 10 and into feed stream 30 via loop 159.

The EDI units of FIG. 2 may share a common concentrate stream in parallel or series via the loop formed from concentrate influent 40 through the first EDI concentrating compartment to first concentrate stream outlet 48 thus forming first concentrate effluent 55, which subsequently flows through second concentrate stream inlet 142 through the second EDI concentrating compartment to second concentrate stream outlet 148 thus forming second concentrate effluent 155 (brine). A portion of second concentrate effluent 155 may be discarded as blowdown stream 156 (brine blowdown), and the remainder recycled into concentrate influent 40 via loop 157 (brine makeup).

EDI unit 100 may be completely independent of EDI unit 10 or both units may reside in the same EDI stack, even between the same pair of electrodes. EDI units 10 and 100 may also consist of two or more EDI devices in series and/or in parallel. Each of such devices may also reside in a single EDI stack, even between the same pair of electrodes. ED and EDI devices may be similarly combined.

In one exemplary embodiment, a conventional type EDI unit 100 can be modified to incorporate partway along the stack an isolator and plumbing to establish two sub-stacks, each with their own separate inlet and outlet manifolds. The outlet manifold of the diluting compartments of

the first sub-stack communicates via a coupler with the inlet manifold of the diluting compartments of the second sub-stack. Such a coupler provides the bond-breaking agent, such as, for example, UV radiation, for converting the non-ionized or non-ionizable organic carbon compounds to ionic or ionizable organic carbon compounds. Thus, this exemplary embodiment including, *inter alia*, the two sub-stacks and the coupler providing the bond-breaking agent forms an integrated system which can be operated on a integrated, continuous basis.

Those of skill in the art will recognize that a wide variety of configurations are available for the concentrate streams of multistage EDI device. Any concentrate stream configuration may be used in accordance with the present invention.

The following examples illustrate preferred modes of making and practicing the invention, but are not meant to limit the scope of the invention, since alternative methods may be employed to obtain similar results.

EXAMPLE 1

A 60 cell pair electrodeionization (EDI) stack (40" x 20") having a 20 gallon per minute capacity (available from Ionics, Incorporated, Watertown, MA) is placed in fluid communication with a portion of a waste stream of a steam generator. A 10 μ cartridge filter is placed upstream of the EDI unit to remove particulate materials. Fluid is pumped into the EDI unit diluting streams by a pressure regulated feed pump. Brine is circulated through the EDI unit by a brine pump. The EDI unit removes, *inter alia*, ionized and ionizable carbon compounds but not non-ionized and non-ionizable carbon compounds. The EDI product is pumped through an ionizing unit including a low pressure mercury arc element for exposing the EDI product to UV radiation including 184.9 nm, and into a regenerated mixed ion exchange (IX) resin deionizing bed. EDI brine conductivity, deionized product resistivities and temperatures are measured using on-line conductivity meters (Thornton 770, Waltham, MA). Feed and brine pH are measured using a handheld pH meter (HYDAC). Organic carbon compounds in the form of ethanolamine (ETA) and methoxypropylamine (MPA) are measured using an organic carbon compound analyzer (Model DC-180, Dohrmann) and independently by NWT Corporation, San Jose, CA.

In FIG. 3, approximate concentrations in parts per million (ppm) of the organic carbon compounds of the EDI unit feed stream "■", the EDI unit product stream "◆", the product stream from the EDI unit in sequence with the IX resin bed "X", and the product stream from the EDI unit in sequence with the ionizing unit followed by the IX resin bed "▲" (after UV and IX), are plotted

against the time of operation of the EDI unit (hours). In this figure, the UV and IX system provides measurements made in accordance with the present invention. FIG. 3 demonstrates that the UV and IX system produces a product stream containing approximately 54% less organic carbon compounds that the product stream of the deionization systems including the EDI unit alone, or the EDI unit in sequence with an ion exchange resin bed without an intermediate organic carbon compound ionizing step. The mixed bed ion exchange unit may be replaced by an EDI (or other ionized and ionizable carbon compound removal) unit producing similar results.

EXAMPLE 2

A split stream of a closed loop water system can be treated by the two-stage deionization device of the invention. In a closed loop, thermal breakdown of ionizable organic species may create some non-ionized and/or non-ionizable organic carbon compounds at a constant rate (r). The application of the deionization-ionization-deionization device of the invention can maintain the loop organic carbon concentration (C) at a low level. Where the split stream flow rate is F , the water recovery rate of the deionization-ionization-deionization device is q , and the organic carbon compound rejection rate by the device is R , then the steady state concentration of the organic carbon can be calculated according to the following equation:

$$r = FC(1 - q + R)$$

For example, in the case where the generation rate of non-ionized and non-ionizable organic carbon is 1984 ppb-gpm, the split stream flow rate is 100 gpm, and the water recovery rate is 95%, then the loop organic carbon concentration is determined in accordance with the relation:

$$C = \frac{1984 \text{ ppb-gpm}}{100 \text{ gpm} (1 - 0.95 + R)}$$

Thus, when $R=0$, i.e., no removal of organic carbon occurs, then the steady state organic carbon concentration $C=396.8$ ppb. When $R=0.25$, then $C=66.1$ ppb; and when $R=0.54$, then $C=33.6$ ppb. FIG. 4 is a representative curve generated in this manner to predict closed loop organic carbon concentration in accordance with the invention.

Although a few exemplary embodiments of this invention have been described in detail above, those skilled in the art will readily appreciate that many modifications are possible in the

exemplary embodiments without materially departing from the novel teachings and advantages of this invention. For example, a variety of ionizing devices and/or methods may be used to ionize organic species which exist in the product of the first deionizing device. Accordingly, all such modifications are intended to be included within the scope of this invention as defined in the

5 following claims.

CLAIMS

1. A method for removing both (i) ionizable and/or ionized carbon compounds and (ii) non-ionized and/or non-ionizable carbon compounds from water comprising the steps of

(a) processing a first stream of the water with a removal apparatus for removing ionized
5 and/or ionizable carbon compounds from the water to produce a first product stream;

(b) contacting the first product stream with an agent for converting non-ionized and/or non-ionizable carbon compounds into ionized and/or ionizable carbon compounds to form a second product stream;

(c) processing the second product stream with a second removal apparatus for removing
10 ionized and/or ionizable carbon compounds from the water to form a third product stream; and

(d) recovering the third product stream from step (e).

2. A method according to claim 1 wherein the first removal apparatus comprises the second removal apparatus.

15

3. A method according to claim 1 wherein the first removal apparatus is selected from the group consisting of a reverse osmosis apparatus, nanofiltration apparatus, ion exchange apparatus, electrically regenerated ion exchange apparatus, electrodeionization apparatus, electrodialysis apparatus, filled cell electrodialysis apparatus, electrodiagnosis apparatus, activated
20 carbon apparatus and other sorbent apparatus.

4. A method according to claim 1, wherein the agent is an oxidizing agent.

5. A method according to claim 4 wherein the oxidizing agent is selected from the group
25 consisting of a chemical oxidizing agent, electrolytic oxidizing agent, electrochemical oxidizing agent, catalytic oxidizing agent, thermal oxidizing agent, and radiation.

6. A method according to claim 4 wherein the oxidizing agent comprises radiation.

30 7. A method according to claim 6 wherein the radiation is ultraviolet radiation.

8. A method according to claim 6 wherein the radiation is characterized by wavelengths of about 254 nm and the oxidizing agent further comprises a catalyst.

9. A method according to claim 8 wherein the radiation is characterized by wavelengths of about 184.9 nm.

10. A method according to claim 6 wherein the oxidizing agent further comprises a catalyst.

11. A method according to claim 10 wherein the catalyst is titanium oxide.

12. An apparatus for removing both (i) ionizable and/or ionized carbon compounds and (ii) non-ionized and/or non-ionizable carbon compounds from water comprising

(a) a first removal means for removing ionized and/or ionizable carbon compounds from the water to produce a first product stream;

(b) a conversion means for converting non-ionized and/or non-ionizable carbon compounds in the first product stream into ionized and/or ionizable carbon compounds to form a second product stream;

(c) a second removal means for removing ionized and/or ionizable carbon compounds from the second product stream to form a third product stream; and

(d) a recovery means for recovering the third product stream.

13. An apparatus according to claim 12 wherein the first removal means comprises the second removal means.

14. An apparatus according to claim 12 wherein the first removal device is selected from the group consisting of a reverse osmosis device, nanofiltration device, ion exchange device, electrically regenerated ion exchange device, electrodeionization device, electrodialysis device, filled cell electrodialysis device, electrodiuresis device, activated carbon device and other sorbent device.

15. An apparatus according to claim 12 wherein the conversion means comprises contact means for contacting the first product stream with an agent.

16. An apparatus according to claim 15 wherein the agent is an oxidizing agent.

17. An apparatus according to claim 16 wherein the oxidizing agent is selected from the group consisting of a chemical oxidizing agent, electrolytic oxidizing agent, electrochemical oxidizing agent, catalytic oxidizing agent, thermal oxidizing agent, and radiation.
- 5 18. An apparatus according to claim 16 wherein the oxidizing agent comprises radiation.
19. An apparatus according to claim 18 wherein the radiation is ultraviolet radiation.
20. An apparatus according to claim 18 wherein the radiation is characterized by
10 wavelengths of about 254 nm and wherein the oxidizing agent further comprises a catalyst.
21. An apparatus according to claim 20 wherein the radiation is characterized by wavelengths of about 184.9 nm.
- 15 22. An apparatus according to claim 16 wherein the oxidizing agent comprises a catalyst.
23. An apparatus according to claim 22 wherein the catalyst is titanium oxide.

1 / 3




FIG. 1
(PRIOR ART)






FIG. 2

**FIG. 3****FIG. 4**

INTERNATIONAL SEARCH REPORT

 International application No.
 PCT/US98/12823

A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) : B01D 61/00, 15/00

US CL : Please See Extra Sheet.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 210/652, 638, 760,644, 661, 663, 900, 263, 195.2, 257.2, 204/157.62, 164

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X --- Y	US 4,863,608 A (KAWAI et al) 05 September 1989, entire disclosure.	1-7, 11-19, 22-23 ----- 8-9, 2-21
X	US 4,280,912 A (BERRY III et al) 28 July 1981, columns 1-6.	1-7, 12-19
Y	US 4,430,226 A (HEDGE et al) 07 February 1984, columns 1-2, column 3, lines 1-15.	1-7, 12-19
X --- Y	US 3870,033 A (FAYLOR et al) 11 March 1975, figures, elements 88,86, 90, columns 1-10.	1, 4-7, 12, 15-19 ----- 3, 4,13-14, 20-21

☒ Further documents are listed in the continuation of Box C.
 ☐ See patent family annex.

* Special categories of cited documents.	*T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
A document defining the general state of the art which is not considered to be of particular relevance	*X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
E earlier document published on or after the international filing date	*Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*Z* document member of the same patent family
O document referring to an oral disclosure, use, exhibition or other means	
P document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

18 SEPTEMBER 1998

Date of mailing of the international search report

29 OCT 1998

 Name and mailing address of the ISA/US
 Commissioner of Patents and Trademarks
 Box PCT
 Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

ANA FORTUNA

Telephone No. (703) 308-3857

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US98/12823

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 4,160,727 A (HARRIS, Jr) 10 July 1979, entire disclosure.	1-7, 12-19

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US98/12823

A. CLASSIFICATION OF SUBJECT MATTER:

US CL :

210/652, 638, 760,644, 661, 663, 900, 263, 195.2, 257.2, 204/157.62, 164

CLAIMS

1. A method for removing both (i) ionizable and/or ionized carbon compounds and (ii) non-ionized and/or non-ionizable carbon compounds from water comprising the steps of

(a) processing a first stream of the water with a removal apparatus for removing ionized and/or ionizable carbon compounds from the water to produce a first product stream;

(b) contacting the first product stream with an agent for converting non-ionized and/or non-ionizable carbon compounds into ionized and/or ionizable carbon compounds to form a second product stream;

(c) processing the second product stream with a second removal apparatus for removing ionized and/or ionizable carbon compounds from the water to form a third product stream; and

(d) recovering the third product stream from step (e).

2. A method according to claim 1 wherein the first removal apparatus comprises the second removal apparatus.

3. A method according to claim 1 wherein the first removal apparatus is selected from the group consisting of a reverse osmosis apparatus, nanofiltration apparatus, ion exchange apparatus, electrically regenerated ion exchange apparatus, electrodeionization apparatus, electrodialysis apparatus, filled cell electrodialysis apparatus, electrodiagnosis apparatus, activated carbon apparatus and other sorbent apparatus.

4. A method according to claim 1, wherein the agent is an oxidizing agent.

5. A method according to claim 4 wherein the oxidizing agent is selected from the group consisting of a chemical oxidizing agent, electrolytic oxidizing agent, electrochemical oxidizing agent, catalytic oxidizing agent, thermal oxidizing agent, and radiation.

6. A method according to claim 4 wherein the oxidizing agent comprises radiation.

7. A method according to claim 6 wherein the radiation is ultraviolet radiation.

8. A method according to claim 6 wherein the radiation is characterized by wavelengths of about 254 nm and the oxidizing agent further comprises a catalyst.

9. A method according to claim 8 wherein the radiation is characterized by wavelengths of about 184.9 nm.

10. A method according to claim 6 wherein the oxidizing agent further comprises a catalyst.

11. A method according to claim 10 wherein the catalyst is titanium oxide.

12. An apparatus for removing both (i) ionizable and/or ionized carbon compounds and (ii) non-ionized and/or non-ionizable carbon compounds from water comprising

(a) a first removal means for removing ionized and/or ionizable carbon compounds from the water to produce a first product stream;

(b) a conversion means for converting non-ionized and/or non-ionizable carbon compounds in the first product stream into ionized and/or ionizable carbon compounds to form a second product stream;

(c) a second removal means for removing ionized and/or ionizable carbon compounds from the second product stream to form a third product stream; and

(d) a recovery means for recovering the third product stream.

13. An apparatus according to claim 12 wherein the first removal means comprises the second removal means.

14. An apparatus according to claim 12 wherein the first removal device is selected from the group consisting of a reverse osmosis device, nanofiltration device, ion exchange device, electrically regenerated ion exchange device, electrodeionization device, electrodialysis device, filled cell electrodialysis device, electrodiagnosis device, activated carbon device and other sorbent device.

15. An apparatus according to claim 12 wherein the conversion means comprises contact means for contacting the first product stream with an agent.

16. An apparatus according to claim 15 wherein the agent is an oxidizing agent.

17. An apparatus according to claim 16 wherein the oxidizing agent is selected from the group consisting of a chemical oxidizing agent, electrolytic oxidizing agent, electrochemical oxidizing agent, catalytic oxidizing agent, thermal oxidizing agent, and radiation.

5 18. An apparatus according to claim 16 wherein the oxidizing agent comprises radiation.

19. An apparatus according to claim 18 wherein the radiation is ultraviolet radiation.

20. An apparatus according to claim 18 wherein the radiation is characterized by
10 wavelengths of about 254 nm and wherein the oxidizing agent further comprises a catalyst.

21. An apparatus according to claim 20 wherein the radiation is characterized by wavelengths of about 184.9 nm.

15 22. An apparatus according to claim 16 wherein the oxidizing agent comprises a catalyst.

23. An apparatus according to claim 22 wherein the catalyst is titanium oxide.